भारतीय प्रौद्योगिकी संस्थान

INDIAN INSTITUTE OF TECHNOLOGY

(काशी हिन्दू विश्वविद्यालय) (BANARAS HINDU UNIVERSITY)

रासायनिक अभियांत्रिकी एवं प्रौद्योगिकी विभाग DEPARTMENT OF CHEMICAL ENGINEERING & TECHNOLOGY

(वाराणसी - २२१००५) Varanasi - 221005

Ref: ChE/2019-20/VS/15

ANNEXURE-I

DEPARTMENT OF CHEMICAL ENGINEERING

INDIAN INSTITUTE OF TECHNOLOGY (BHU) VARANASI

<u>ENQUIRY</u>

Due Date: 23 Aug 2019

Date: 02 Aug 2019

Date: 02 Aug 2019

Dear Sir,

Please submit your lowest quotation for supplying the under mentioned items. Quotation must reach us before the date marked above and should contain the following information:

- 1. Full specification and make of the item offered and its rate F.O.R. Varanasi/CIF New Delhi.
- 2. Sales tax at concessional rate as applicable to educational institution.
- 3. Your sales tax registration number and TAN number.
- 4. Conditions of supply and terms of payment.
- 5. If you are a manufacture of the item or if you have proprietary right over it, please mention it in the quotation and provide a certificate.
- 6. Please mention your agency commission in Indian currency. If applicable (in case of imported items).
- 7. Please give undertaking as per annexure-I-B

Quotation must be sent in a **sealed envelope** with word "QUOTATION", our reference number, and due date as given above, clearly marked over it to the address: Dr. Vijay Shinde, Assistant Professor, Department of Chemical Engineering, Indian Institute of Technology (BHU) VARANASI 221005.

Technical Specifications: Fluidised Bed Reactor

1. Reactor and furnace assembly	2. Gas Feed Assembly
1.1 Reactor: 01 set	2.1 Flow Controller: 03 set
Type: Fluidised bed reactor	Gas: Ar/N_2 , $CH_4/CO/C_3H_8$, CO_2
Catalyst: Al ₂ O ₃ (80 μm)	Flow : 5-50 SLPH
Catalyst of weight : 20-30 g	Operating Pressure: 5 Bar
Heating Length : whole reactor	Operating Temperature: Ambient
Operating Pressure: 1 Bar	2.2 Pre-heater: 01 set
Design Pressure: 5 Bar	Type: Tubular type.
Operating Temperature : 700 Deg C	Design Pressure: 5 Bar
Design Temperature: 750 Deg C	Operating Temperature: 300 Deg C
MOC: SS316	MOC: SS 316
1.2. Furnace: 01 set	
Type: Vertical tubular type	4. Down Stream Section
Dimensions: Suitable for the reactor dimensions.	4.1 Gas solid separator: 01 set
Operating Temperature: 800 Deg C	Capacity: 1 liter
	Design Pressure: 5 Bar
3. Liquid Feed Assembly: 01 set	Operating Pressure: 1 Bar
3.1 Feed Vessel: 01 set	4.2 Condenser: 01 set
Capacity: 1 Liter	Type: Spiral
Operating Pressure: Atmospheric	Design Pressure: 5 Bar



भारतीय प्रौद्योगिकी संस्थान



INDIAN INSTITUTE OF TECHNOLOGY

(काशी हिन्दू विश्वविद्यालय) (BANARAS HINDU UNIVERSITY)

रासायनिक अभियांत्रिकी एवं प्रौद्योगिकी विभाग

DEPARTMENT OF CHEMICAL ENGINEERING & TECHNOLOGY

(ऊच्चानुशीलन केन्द्र एवं डी एस टी प्रायोजित 'फिस्ट' विभाग) (CENTRE OF ADVANCED STUDY & DST DEPARTMENT UNDER FIST) (वाराणसी - २२१००५) Varanasi - 221005

Operating Temperature: Ambient	Operating Pressure : 1 Bar
MOC: Glass	MOC: Suitable (preferred SS316)
3.2 Feed Pump: 01 set	4.3 Gas Liquid Separator: 01 set
Type: Piston	Type: Closed end on top, torispherical dish end
Flow Rate: 1-30 ml/h	on bottom.
Capacity of tank: 500 ml	Capacity: 1 liter
Operating pressure: 0-5 Bar	Operating Pressure: 1 Bar
Operating Temperature: Ambient	MOC: Suitable
MOC: SS 316	
3.3 Vaporizer: 01 set	6. Valves
Type: Tube type	Filter (for gas and liquid lines), Isolation Valve
Design Pressure: 5 Bar	(2/3 ways), Needle Valve, Non-Return valve,
Operating Temperature: Ambient	Pressure safety relief valve etc.: As per
MOC: SS 316	requirement.
	MOC: SS 316
5. Instruments	
5.1 Pressure gauge: As per requirement.	7. Fittings & Tubing: As per requirement
Type: Bourdon	
Pressure Range: 0-5 Bar	8. PID based Control Panel
	Preheater, Reactor's temperature controller, Gas
5.2 Temperature thermocouples: As per	Flow controllers, & pressure indication
requirement	
Туре: К-tуре	9. Structure: Aluminium/Iron
Temperature Range: 0-800 Deg C	
	10. Desktop for data logging
5.3 Differential Pressure regulator: 01 set	
Pressure: 0-5 Bar	11. Gas Cylinders
	10% CH ₄ (balance Argon), 10% Propane (balance
12. Double stage pressure regulators for the gas	Argon) and Pure argon gas cylinders filled with
cylinders mentioned in 11 (SS Dianhragm	UHP gases.
cymaers mentioned in II. (55 Diapinagin,	Valid Explosive License Certificate for each
Gauges)	cylinder.
	Capacity: 47 ltrs.

Other non-technical specifications

- 1. P&ID Diagram must be provided along with this enquiry.
- 2. Supplier must have supplied the aforementioned item to IITs/Central Universities in India.
- 3. At least one customer satisfaction certificate is required.

HOD/COS/PI