



Ref. No.: IIT(BHU)/IWD/CT-03/2021-22/667 Dated: **21.09.2021** 

# **QUOTATION NOTICE**

1. Limited tender quotations are invited from UWD, BHU empaneled contractors and those contractors who had worked in erstwhile IT(BHU) before conversion i.e. 29.06.2012 for P/F aluminium partition, false ceiling and painting work in the lab of Dr. Rosy, Department of Chemistry, IIT(BHU) Varanasi as per description below. The sealed envelope containing quotation shall be superscribed with the name of the work, tender enquiry ref. no. & date. The quotations will be received up to 3:00 P.M on or before 29.09.2021 (3:00 P.M.) in the office of the Superintending Engineer, Institute Works Department, IIT(BHU), Varanasi.

|      | Parametrian of items   | <u> </u> | _   |      | Date | A |           |        |
|------|--|----------|-----|------|------|---|-----------|--------|
| S.No | Description of items   | Qty.     |     | Qty. |      |   | Rate Amou | Amount |
| 1    | Removing dry or oil bound distemper, water proffing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc.   |          |     |      |      |   |           |        |
|      | complete (14.46)   | 69.00    | sqm |      | sqm  |   |           |        |
| 2    | Providing and applying white cement based putty of average thickness 1mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth   |          |     |      |      |   |           |        |
|      | complete. (13.80)  | 69.00    | sqm |      | sqm  |   |           |        |
| 3    | Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade   |          |     |      |      |   |           |        |
|      | New work (two or more coats) over and including water thinnable priming coat with cement primer (13.41.1)  | 69.00    | sqm |      | sqm  |   |           |        |
| 4    | Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:   |          |     |      |      |   |           |        |
|      | One or more coats on old work. (14.54.1)   | 16.00    | sqm | Щ    | sqm  |   |           |        |
| 5    | Providing and fixing false ceiling at all heights with integral densified calcium silicate reinforced with fibre and natural filler false ceiling tiles of Size 595x595 mm of approved texture, design and patterns having NRC (Noise Reduction coefficient) of 0.50 (minimum) as per IS 8225:1987, Light reflectance of 85% (minimum). Non combustible as per BS:476 (part-4), fire performance as per BS:476 (part 6 &7), humidity resistance of 100%, thermal conductivity < 0.043 W/m K as per ASTM 518:1991,in true horizontal level suspended on interlocking metal T-Grid of hot dipped galvanised iron section of 0.33mm thick (galvanized @ 120 grams per sqm including both sides) comprising of main-T  |          |     |      |      |   |           |        |
|      | runners of size 24x38 mm of length 3000 mm, cross - T of size 24x32 mm of length 1200 mm and secondary intermediate cross-T of size 24x32 mm of length 600mm to form grid module of size 600 x 600 mm, suspended from ceiling using galvanised mild steel items (galvanizing @ 80 grams per sqm) i.e. 50 mm long, 8 mm outer diameter M-6 dash fasteners, 6 mm dia fully threaded hanger rod upto 1000 mm length and L-shape level adjuster of size 85x25x25x2 mm. Galvanised iron perimeter wall angle of size 24x24x0.40 mm of length 3000 mm to be fixed on periphery wall / partition with the help of plastic rawl plugs at 450 mm center to center and 40 mm long dry wall S.S screws. The work shall be carried out as per specifications, drawing and as per directions of Engineer-in-Charge. |          |     |      |      |   |           |        |
|      | With 15 mm thick tegular edged light weight calcium silicate false ceiling tiles. (26.22.1)  | 24.00    | sqm |      | sqm  |   |           |        |



| 6 Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate 2 sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fastners of required dia & size, including necessary filling up the gaps at junctions, i.e. top, bottom and sides with required EPDM rubber /neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle. Aluminium snap beading for glazing / panelling, CP. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing and panelling to be paid for separately).  (a) For fixed portion  Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) (21.1.1.1)  7 Providing and fixing 12mm thick prelaminated particle board flat pressed three layer or garded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminium doors, windows shutters and partitions for engineer-in-charge.  Pre-laminated particle board with decorative lamination on one side and balancing lamination on other side (21.2.1)  8 Providing and fixing glazing in aluminium door, windows, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item.)  With float glass panes of 5.50 mm thickness (21.3.2)  9 Providing and fixing jaluminium handless ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade with necessary screws etc. complete: (21.13)  10 Providing and fixing aluminium handless ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with necessary screws e |       | institute works Departi  |        |      |      |  |
|--|-------|--|--------|------|------|--|
| shade according to IS: 1868, Minimum anodic coating of grade AC 15) (21.1.1.1)  7 Providing and fixing 12mm thick prelaminated particle board flat pressed three layer or garded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminium doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge.  Pre-laminated particle board with decorative lamination on one side and balancing lamination on other side (21.2.1)  8 Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item.)  With float glass panes of 5.50 mm thickness (21.3.2)  9 Providing and fixing aluminium handles ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade with necessary screws etc. complete:  125 mm (9.100.1)  10 Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete. (21.13)  11 Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with ISI, IS:3564, embossed on the body, door weight upto 36 kg to 80 kg and door width from 701mm to 1000mm), with double speed adjustment with necessary accessories and screws etc. complete. (9.84)  12 Providing and fixing aluminium hanging floor door stopper ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with necessary screws etc. complete.  Twin rubber stopper (9.101.2)  13 Providing and fixing fly proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with  | 6     | Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fastners of required dia & size, including necessary filling up the gaps at junctions, i.e. top, bottom and sides with required EPDM rubber /neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing and panelling to be paid for separately.)  (a) For fixed portion |        |      |      |  |
| Providing and fixing 12mm thick prelaminated particle board flat pressed three layer or garded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminium doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge.  Pre-laminated particle board with decorative lamination on one side and balancing lamination on other side (21.2.1)  8 Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item.)  With float glass panes of 5.50 mm thickness (21.3.2)  9 Providing and fixing aluminium handles ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade with necessary screws etc. complete:  125 mm (9.100.1)  10 Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete. (21.13)  11 Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with ISI, IS:3564, embossed on the body, door weight upto 36 kg to 80 kg and door width from 701mm to 1000mm), with double speed adjustment with necessary accessories and screws etc. complete. (9.84)  12 Providing and fixing aluminium hanging floor door stopper ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with necessary screws etc. complete.  Twin rubber stopper (9.101.2)  13 Providing and fixing fly proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia. 0.50 mm all complete.  With 2nd class teak wood beading 62X19 mm (9.1 |       | shade according to IS: 1868, Minimum anodic coating of grade   | 125.00 | kg   | kg   |  |
| side and balancing lamination on other side (21.2.1)  Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item.)  With float glass panes of 5.50 mm thickness (21.3.2)  Providing and fixing aluminium handles ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade with necessary screws etc. complete:  125 mm (9.100.1)  Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc.complete. (21.13)  10 Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with ISI, IS:3564, embossed on the body, door weight upto 36 kg to 80 kg and door width from 701mm to 1000mm), with double speed adjustment with necessary accessories and screws etc. complete. (9.84)  12 Providing and fixing aluminium hanging floor door stopper ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with necessary screws etc. complete.  Twin rubber stopper (9.101.2)  13 Providing and fixing proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia. 0.50 mm all complete.  With 2nd class teak wood beading 62X19 mm (9.135.1)  3.00 sqm sqm  Total Rs.   | 7     | Providing and fixing 12mm thick prelaminated particle board flat pressed three layer or garded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminium doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge.  |        | J    | J    |  |
| ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item.)  With float glass panes of 5.50 mm thickness (21.3.2)  9 Providing and fixing aluminium handles ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade with necessary screws etc. complete:  125 mm (9.100.1)  10 Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc.complete. (21.13)  11 Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with ISI, IS:3564, embossed on the body, door weight upto 36 kg to 80 kg and door width from 701mm to 1000mm), with double speed adjustment with necessary accessories and screws etc. complete. (9.84)  12 Providing and fixing aluminium hanging floor door stopper ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with necessary screws etc. complete.  Twin rubber stopper (9.101.2)  2 Nos Each  13 Providing and fixing fly proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia. 0.50 mm all complete.  With 2nd class teak wood beading 62X19 mm (9.135.1)  3 .00 sqm sqm  |       | side and balancing lamination on other side (21.2.1)   | 8.00   | sqm  | sqm  |  |
| 9 Providing and fixing aluminium handles ISI marked anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with necessary screws etc. complete:  125 mm (9.100.1) 6 Nos Each  10 Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc.complete. (21.13) 1 Nos Each  11 Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with ISI, IS:3564, embossed on the body, door weight upto 36 kg to 80 kg and door width from 701mm to 1000mm), with double speed adjustment with necessary accessories and screws etc. complete. (9.84) 2 Nos Each  12 Providing and fixing aluminium hanging floor door stopper ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with necessary screws etc. complete.  Twin rubber stopper (9.101.2) 2 Nos Each  13 Providing and fixing fly proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia. 0.50 mm all complete.  With 2nd class teak wood beading 62X19 mm (9.135.1) 3.00 sqm sqm   | 8     | ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium  |        |      |      |  |
| (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with necessary screws etc. complete:  125 mm (9.100.1)  Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc.complete. (21.13)  1 Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with ISI, IS:3564, embossed on the body, door weight upto 36 kg to 80 kg and door width from 701mm to 1000mm), with double speed adjustment with necessary accessories and screws etc. complete. (9.84)  2 Nos Each  12 Providing and fixing aluminium hanging floor door stopper ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with necessary screws etc. complete.  Twin rubber stopper (9.101.2)  2 Nos Each  13 Providing and fixing fly proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia. 0.50 mm all complete.  With 2nd class teak wood beading 62X19 mm (9.135.1)  3.00 sqm sqm   |       |  | 10.00  | sqm  | sqm  |  |
| 10 Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc.complete. (21.13)  11 Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with ISI, IS:3564, embossed on the body, door weight upto 36 kg to 80 kg and door width from 701mm to 1000mm), with double speed adjustment with necessary accessories and screws etc. complete. (9.84)  12 Providing and fixing aluminium hanging floor door stopper ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with necessary screws etc. complete.  Twin rubber stopper (9.101.2)  13 Providing and fixing fly proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia. 0.50 mm all complete.  With 2nd class teak wood beading 62X19 mm (9.135.1)  3.00 sqm sqm   | 9     | (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade with necessary   |        |      |      |  |
| quality) for aluminium doors including necessary cutting and making good etc.complete. (21.13)  11 Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with ISI, IS:3564, embossed on the body, door weight upto 36 kg to 80 kg and door width from 701mm to 1000mm), with double speed adjustment with necessary accessories and screws etc. complete. (9.84)  12 Providing and fixing aluminium hanging floor door stopper ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with necessary screws etc. complete.  Twin rubber stopper (9.101.2)  2 Nos Each  13 Providing and fixing fly proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia. 0.50 mm all complete.  With 2nd class teak wood beading 62X19 mm (9.135.1)  3.00 sqm sqm  |       |  | 6      | Nos  | Each |  |
| 11 Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with ISI, IS:3564, embossed on the body, door weight upto 36 kg to 80 kg and door width from 701mm to 1000mm), with double speed adjustment with necessary accessories and screws etc. complete. (9.84)  12 Providing and fixing aluminium hanging floor door stopper ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with necessary screws etc. complete.  Twin rubber stopper (9.101.2)  2 Nos Each  13 Providing and fixing fly proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia. 0.50 mm all complete.  With 2nd class teak wood beading 62X19 mm (9.135.1)  3.00 sqm sqm  | 10    | quality) for aluminium doors including necessary cutting and   | 1      | Nos  | Each |  |
| 12 Providing and fixing aluminium hanging floor door stopper ISI marked anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with necessary screws etc. complete.  Twin rubber stopper (9.101.2)  13 Providing and fixing fly proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia. 0.50 mm all complete.  With 2nd class teak wood beading 62X19 mm (9.135.1)  3.00 sqm sqm   | 11    | Providing and fixing aluminium extruded section body tubular type universal hydraulic door closer (having brand logo with ISI, IS:3564, embossed on the body, door weight upto 36 kg to 80 kg and door width from 701mm to 1000mm), with double speed adjustment with necessary accessories and screws etc.  |        |      |      |  |
| with necessary screws etc. complete.  Twin rubber stopper (9.101.2)  13 Providing and fixing fly proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia. 0.50 mm all complete.  With 2nd class teak wood beading 62X19 mm (9.135.1)  3.00 sqm sqm  Total Rs.   | 12    | Providing and fixing aluminium hanging floor door stopper ISI marked anodised (anodic coating not less than grade AC 10 as   |        | INOS | Each |  |
| Providing and fixing fly proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia. 0.50 mm all complete.  With 2nd class teak wood beading 62X19 mm (9.135.1)  3.00 sqm sqm  Total Rs.   |       | with necessary screws etc. complete.   | 2      | Nos  | Faak |  |
| Total Rs.  | 13    | Providing and fixing fly proof stainless steel grade 304 wire gauge, to windows and clerestory windows using wire gauge with average width of aperture 1.4 mm in both directions with wire of dia. 0.50 mm all complete.   |        |      |      |  |
|  | T-4-1 |  | 3.00   | sqm  | sqm  |  |
|  | lotal |  |        |      |      |  |

2. The bidders should submit self certified order copies of similar type of construction works executed during last three financial years alongwith self certified copies of satisfactory work completion certificates.



- 3. Those bidders who have already executed similar type of works in IWD, IIT(BHU) need not submit satisfactory work completion certificates. They should submit only the self certified copies of earlier work orders.
- 4. The amount of similar work order executed during preceding last three financial years should be at least:
- (i) 1 order of 80% of estimated cost of this work.

OR

(ii) 2 order of 60% of estimated cost of this work.

OR

- (iii) 3 order of 40% of estimated cost of this work.
- 5. (a) Intending bidder should have average annual financial turnover of at least 30% of the estimated cost of this works during preceding last three financial years. Self-certified photocopies of certificate from CA to be submitted with bid.
  - (b) Should not have incurred any loss in more than three years during the preceding three financial years ending 31<sup>st</sup> March, 2021. Self-Certified photocopy of certificate from CA to be submitted alongwith last three years Profit & Loss Account to be submitted with bid.
  - (c) Should have a solvency certificate of 40% of the estimated cost issued by Bank during the last six months. Certified copy of original solvency certificate to be submitted with bid.
- 6. Any bid submitted without the above-mentioned documents in support of criteria laid down from Sl. No. 2 to 5 above shall be treated as unresponsive and may not be considered for further evaluation by the tender opening committee.
- 7. The quotation forms complete in all aspects along with all required documents should be submitted in sealed envelope along with **tender fee of Rs. 500.00 + Rs. 90.00 (GST @ 18%) = Rs. 590.00** in the form of demand draft drawn in favour of the Registrar, IIT (BHU), payable at Varanasi.
- 8. The estimated cost of this work is **Rs. 1,17,460.60**. The **Earnest Money Deposit** of **Rs. 4,000.00** shall be submitted in the form of FDR or DD in favour of the Registrar, IIT(BHU), payable at Varanasi. The **EMD** of successful bidder will be retained until the completion of work and shall be returned after the payment of final bill & deduction of security deposit. The EMD of unsuccessful bidders shall be returned after the final award of work.
- 9. In case of tie between two or more bidders at L-1 price, all L-1 bidders shall be asked to resubmit their bids in sealed envelope with the objective to break the tie to obtained a single L-1 bidder.
- 10. The works will be executed on Agreement/work order basis.



- 11. Institute reserves the right to reject any quotation or all quotation without prejudice, prior notice, or any explanation/justification.
- 12. If a quotation is submitted without mentioning explicit rate of each item, quotation will not be considered for further processing.
- 13. Quotation(s), if not duly signed by the contractor or his legally authorized partner, if any, will be considered invalid.
- 14. Security deposit @5% shall be deducted from each bill. The security deposit of 5% deducted from all the bills will be refunded after completion of the defect liability period, i.e., 01 years from the date of payment of final bill and confirmation of no defect from IWD engineering wing. The date of work completion will be counted as the date of payment of final bill.

A retention amount of @ 10% of the gross amount of the bill shall be deducted from each running bill of the bidder till the sum along with sum already deposited as earnest money, will amount to Security Deposit of 5% of the tender value of the work.

- 15. 1% water tax will be deducted from each bill, wherever applicable.
- 16. Electricity charge will be deducted as per the actual consumption.
- 17. 2% Income Tax and other applicable taxes such as GST etc. shall be deducted as per applicable Govt. rules.
- 18. <u>Amount and quantity variation</u>: Quantity may vary as per actual work execution/site requirement/end user suggested changes during execution but the final bill value shall not exceed more than 5% of order value.
- 19. Work completion period: Within 60 Days from the issue of the work order/date of agreement. A period of 03 days will be added to the allocated period for the completion of this work.
- 20. <u>Late work completion penalty</u>: If work is not completed within the given time, penalty will be deducted as per institute norms. It will be implemented in verbatim with no excuse to be entertained for whatsoever be the reason.
- 21. Any damage caused to the building shall have to be made good by contractor at no extra cost & without any delay.



- 22. Site must be cleared, and made neat and clean. Any waste material resulted out of the work execution must be disposed of to the specified location identified by the Assistant Engineer, IWD. If not, 1% extra charges shall be deducted from the bill to dispose of the malba.
- 23. Duly completed tender document alongwith Quotation form, tender fee & E.M.D. should be sealed in one envelope, which is superscribed with Name of work, Tender Reference No. & date submitted on or before the last date & time as mentioned at S. No. 1 above.
- 24. The empty containers of paint/adhesive/chemicals etc. used in the work are to be returned to the custody of Assistant Engineer, IWD.
- 25. The bids submitted after the last date & time will not be considered for opening. The bids received within the last date & time will be opened on 30.09.2021 (4:00 P.M.) in the office of Institute Works Department, IIT(BHU), Varanasi.

Sd-Superintending Engineer IWD, IIT(BHU), Varanasi





## **Institute Works Department**

## **QUOTATION FORM**

| Ref. No.: IIT(BHU)/IWD/CT-03/2021-22/667   | Dated: 21.09.2021   |
|--|---|
| The Superintending Engineer Institute Works Department, Indian Institute of Technology (BHU), Varanasi-221005  |   |
| Subject: Quotation for   |   |
|  |   |
|  |   |
| Dear Sir,  |   |
| With reference to the Quotation invited by you for the offer to perform, provide, execute, complete and maintain drawing, conditions of tender, articles of agreement condition quantities of the sum of Rs. (Rupees | in work in conformity with the ons of contract, specification and |
| ) at the respective rates menti  | oned in the quotations.   |
| My/Our quotation will remain open for acceptance f opening.  | for 12 months from the date of its                                |
| I have submitting tender fee of <b>Rs. 590/-</b> vide DD No on   | odateddrawn<br>(Name of Bank).                                    |
| I have submitted EMD of Rs Viddated issued by  |   |
|  |   |
| I have enclosed self attached copy of PAN No. and C  | =   |
| My email id for all future correspondence regarding of work order is and mobile no. is   | this bid including communication                                  |
| (Note: Any information left blank such as email id, mobining lead to rejection of bid as non-responsive)   | ile number, PAN & GSTIN etc.                                      |
|  | Yours faithfully,   |
| Date: (Sig   | nature of contractor with seal)                                   |

